

- MUNICIPAL
- INDUSTRIAL
- CONSTRUCTION / RENTAL
- AGRICULTURE

ULTRAV[®]
SERIES



*High-Head, High Performance,
Self-Priming Trash Pumps*

GR[®]
GORMAN-RUPP
PUMPS

A HISTORY OF INNOVATION



Gorman-Rupp has been revolutionizing the pumping industry since 1933. Many of the innovations introduced by Gorman-Rupp over the years have become industry standards.

More than ever, we continue to update our factories, processes, research and development, and engineering to ensure that our pumps and systems are among the most reliable and efficient in the world. One of our most successful and innovative lines of pumps has been our self-priming models.

Revolutionary improvements were made in 1963 with the introduction of our T Series® self-priming pumps. Since then, continuous improvements to head, flow and efficiency have been made.

In 2000 we introduced our Super T Series® with many added maintenance features to enhance serviceability. And, in 2005, Gorman-Rupp introduced the revolutionary Ultra V Series®

which offers industry-leading performance for self-priming applications

Today, Gorman-Rupp self-priming pumps are the world's leading choice for waste handling applications in industries such as steel and paper mills, mining operations, food processing plants, power plants, automotive factories, tanneries and wineries. They are also the pump of choice in many sewage-handling applications worldwide.

Gorman-Rupp's commitment to our original philosophy of innovation, continuous improvement, unparalleled quality and customer service continues to set us apart from others.

OUR PUMPS DELIVER DECADES OF PERFORMANCE AND VALUE.

Gorman-Rupp is committed to meeting your fluid-handling requirements long after installation. The quality manufacturing and testing that go into every Ultra V Series® pump guarantee long-lasting, trouble-free operation. And we provide a five year warranty and fast parts service to back up our products and ensure your peace of mind.

Make Gorman-Rupp Your Single Source For:

Value

Ultra V Series® pumps boast some of the lowest lifecycle costs in the industry. Because of the quality manufacturing and testing that goes into every Gorman-Rupp product, you benefit from minimal service interruptions and some of the lowest maintenance in the industry. Gorman-Rupp delivers the best ROI by ensuring low operating costs for decades.

Parts and Service

When you need a replacement part for your Ultra V Series, you'll have it fast. With tens of thousands of genuine Gorman-Rupp parts and pumps at our disposal, we fill and ship 97% of parts orders within 24 hours. Should your Ultra V Series pump or ReliaSource® pump package ever require service, our worldwide network of factory-trained distributors is ready to quickly respond to your needs. With just one number to call for parts and service for your entire lift station, it's easy and convenient to keep your equipment performing as it should.

Peace of Mind

At Gorman-Rupp, we don't just say our pumps are reliable. Unlike standard 90-day or one-year warranties, we guarantee every part and working component of a Ultra V Series pump for a full five years. With Gorman-Rupp, reliable performance is always guaranteed.



ULTRA V SERIES® & VS SERIES

*High-Head, High Performance Self-Priming,
Solids-Handling Trash Pumps*



Superior Performance

The Ultra V Series® and VS Series solids-handling, self-priming centrifugal trash pumps offer up to three times the pressure and up to 60% more performance.

Available in a variety of pump station configurations or stand-alone in 3", 4" and 6" sizes. The superior solids-handling and increased pressure capabilities of the Ultra V Series pumps make them ideally suited for a variety of industrial and sewage applications.

Ultra V Series® pumps are available in a variety of drive variations including basic units, trailer mounted engine-driven units, or as part of an engineered ReliaSource® packaged pump station.



Ultra V Series® Pumps Feature:

- Up to three times the pressure
- Up to 60% increased flow
- Greater efficiencies
- Self-cleaning features
- Reduced footprint
- Externally removable suction check valve
- Unique configuration capabilities
- Improved solids-handling

Three Times The Pressure

The patented UltraMate® can be paired with the Ultra V Series pump when system requirements exceed the Ultra V's exceptional performance range. By adding the UltraMate unit directly to the Ultra V through an innovative transition chamber, maximum pressure is increased up to three times the pressure of traditional solids-handling, self-priming, single stage pumps. Losses associated with conventional series connected pumps are also reduced, resulting in increased efficiencies.






Smart Scroll® Discharge Locator

The patented Smart Scroll® can be rotated to fit your specific piping system. It can be ordered in vertical or horizontal facing, left or right positions.



ULTRA V[®]

SERIES



All Ultra V Series[®] pumps feature a standard five-year warranty.



ULTRAMATE[®]

- 1–Removable Suction Check Valve
- 2–Easy-Off Coverplate Nuts
- 3–Pusher Bolt Holes
- 4–Removable Back Coverplate
- 5–Pressure Relief Valve
- 6–Shimless Coverplate Adjustment
- 7–Self-Cleaning Replaceable Wearplate
- 8–Heavy-Duty Impeller
- 9–Cartridge Mechanical Seal
- 10–Atmospheric Bearing Isolation
- 11–Two Double Lip Seals
- 12–Heavy-Duty Bearings
- 13–Oversized Seal Oil Chamber
- 14–Removable Rotating Assembly
- 15–Bearing Oil Sight Gauge
- 16–Seal Oil Sight Gauge
- 17–Removable Rotating Assembly*
- 18–Removable Back Coverplate*
- 19–Smart Scroll[®]
- 20–Transition Chamber
- 21–Fill Port

*Interchangeable with Ultra V rotating assembly

Specifications

Pump Size: 3" (75 mm),
4" (100 mm), 6" (150 mm),
Max. Capacity: 1900 GPM
(119.9 lps)
Max. Solids: 3" (76.2 mm)
Max. Head: 325' (99.1 m)
Materials of Construction:
Cast Iron, 316 Stainless
Steel Fitted, CD4MCu, G-R
Hard Iron Fitted

ECONOMICAL OPERATION EASY TO SERVICE



Gorman-Rupp's patented external shimless adjustment design doubles the life of the impeller and wearplate.

The external shimless coverplate allows for easy adjustment of the clearance between the impeller and the wearplate. This process eliminates the need to realign belts, couplings or other drive components. In turn, the working height of the seal assembly and impeller back clearance are not disturbed. The unique collar and adjusting screw allow for incremental adjustments of the wearplate clearance.

Once adjustments have been made, the collar locks in place, maintaining the clearance setting even if the coverplate is removed. This design feature doubles the life of the impeller and wearplate while maintaining peak operating efficiency.

Easily Removable Coverplate

The removable coverplate with easy-grip handle and pusher bolt capability provides quick and easy access to the pump interior.



Dual Bearing Protection



An atmospheric barrier along with two lip seals provide additional protection of the pump bearings. This unique design also allows for quick and easy external monitoring of the bearing cavity.

Removable Rotating Assembly

The entire rotating assembly can be removed without disturbing the pump volute or piping. Pusher bolt holes are provided to assist with removal. This allows for quick and easy installation of a spare rotating assembly, resulting in less downtime.

Check Valve



A positive sealing, externally removable suction check valve is standard on Ultra V Series® models. This eliminates the need to disconnect any piping for inspection or replacement. The check valve has a blowout center that limits excessive volute pressure, protecting the pump.

Solids-Handling Impeller

The two-vane, semi-open solids handling impeller handles up to 3" (76.2 mm) diameter solids, depending on pump model. Pump out vanes on the impeller shroud reduce foreign material buildup behind the impeller and reduce pressure on the seal and bearings.



Replaceable Wearplate

A replaceable self-cleaning wearplate ensures debris is cleared away and does not collect on the impeller vanes. This innovative design reduces the overall life cycle costs by minimizing blockage within the pump.



Gorman-Rupp Cartridge Seal

The exclusive double-floating, self-aligning, oil lubricated mechanical cartridge seal with silicon carbide stationary and rotating faces is specifically designed for abrasive and/or trash handling service. Consult the factory for additional seal configurations.



GORMAN-RUPP ULTRA V SERIES®

The Right Pump For The Job

Built upon the foundation of the Super T Series®, Gorman-Rupp Ultra V Series® pumps excel in high-head applications where traditional self-priming trash pumps fall short. Available in three sizes, these pumps can be configured as a trailer mounted engine-driven unit or be part of an engineered ReliaSource® pump station that is factory assembled, tested, shipped, and ready for installation.

Basic Pumps



Ultra V Series®
Size: 3" (75 mm)



Ultra V Series®
Size: 4" (100 mm)



Ultra V Series®
Size: 6" (150 mm)



VS Series
Size: 3" (75 mm)



VS Series
Size: 4" (100 mm)



VS Series
Size: 6" (150 mm)

Drive Variations



Ultra V Series®
Engine driven
Shown with optional wheel kit



Ultra V Series®
ReliaSource® packaged
pumping station


Optional Accessories

- Industrial & Municipal ReliaSource® Packages
- Automatic Air Release Valve
- Discharge Check Valve
- Suction & Discharge Flange Kits
- Volute Casing Heater
- Suction & Discharge Gauge Kits
- Complete Replacement Rotating Assembly
- Pump Spare Parts Kit
- Pump Easy Drain Kit
- Custom Seal Options
- Controls & Complete Stations
- Optional Elastomers and Suction Flap Valve Materials (EPDM, Neoprene, AFLAS-TFE, Viton®*)


The V3B and VS3B models offer an optional hydraulic design developed to meet three inch solids-handling requirements in a three inch pump.

Pump Performance Data

Ultra V Series®



VS Series



NOTE: Consult factory for other performance conditions.

*Viton® is a registered trademark of DuPont Performance Elastomers. All rights reserved.

FLUID HANDLING EQUIPMENT DESIGNED WITH YOUR NEEDS IN MIND.

<p>★ Manufacturing Facilities</p> <p>● Distribution Centers</p>	<p>The Gorman-Rupp Company Mansfield, Ohio, USA</p> <p>Mansfield Division Mansfield, Ohio, USA</p> <p>Gorman-Rupp International Mansfield, Ohio, USA</p> <p>Gorman-Rupp Industries Bellville, Ohio, USA</p>	<p>Patterson Pump Company Toccoa, Georgia, USA</p> <p>American Machine and Tool Co., Inc. of Pennsylvania Royersford, Pennsylvania, USA</p> <p>National Pump Company Fresno, California, USA Glendale, Arizona, USA (Headquarters) Lubbock, Texas, USA Olive Branch, Mississippi, USA Vienna, Georgia, USA Zolfo Springs, Florida, USA</p>	<p>★</p> <p>Gorman-Rupp Africa Cape Town, South Africa Durban, South Africa Johannesburg, South Africa (Headquarters)</p> <p>Gorman-Rupp Europe Leeuwarden, Netherlands</p> <p>Patterson Pump Ireland Limited County Westmeath, Ireland</p> <p>Gorman-Rupp of Canada Limited St. Thomas, Ontario, Canada</p>	<p>Distribution Centers Bangkok, Thailand Dubai, United Arab Emirates Grand Prairie, Texas, USA Leeuwarden, Netherlands Sparks, Nevada, USA</p>
---	---	---	--	--

Engineering and manufacturing superiority has been a hallmark of Gorman-Rupp since our inception in 1933. Today we bring our products to life in some of the most efficient, modern and state-of-the-art manufacturing facilities in the world. Gorman-Rupp has a selection of nearly 3,000 pump models, and our world-class team of distributors has worked closely with thousands of end users around the world. We have the proven expertise and the resources to specify, manufacture, test and service your pump, and to ensure reliable performance for the long haul.



GRPUMPS.COM



**THE GORMAN-RUPP COMPANY
MANSFIELD DIVISION**
P.O. BOX 1217
MANSFIELD, OHIO 44901-1217 | USA
TEL: 419.755.1011 | FAX: 419.755.1251
GRSALES@GORMANRUPP.COM

GORMAN-RUPP INTERNATIONAL
P.O. BOX 1217
MANSFIELD, OHIO 44901-1217 | USA
TEL: 419.755.1011 | FAX: 419.755.1266
INTSALES@GORMANRUPP.COM

GORMAN-RUPP OF CANADA
70 BURWELL ROAD
ST. THOMAS, ONTARIO N5P 3R7 CANADA
TEL: 519.631.2870 | FAX: 519.631.4624
GRCANADA@GORMANRUPP.COM